

# Elcotel SERIES-5

1 STOP  
2  
3

5-10-25  
U.S. COINS ONLY

COIN RELEASE

No coin needed for Charge, SOS, & Free calls.

Local calls (except 25c before calling)  
Long Distance Dial all calls directly  
SOS needed for Charge & Personal Personal calls  
SOS needed for Station-to-Station & Free Calls  
SOS dial 911 for Emergency help

1. 25c  
2. 25c

ELCOTEL INC.



Station-to-Station calls	Within this Area Code	Number
	Outside this Area Code	Area Code + Number
Calling Card Calls	Within this Area Code	Area Code + Number
	Outside this Area Code	Area Code + Number
Collect and Person-to-Person calls	Within this Area Code	Area Code + Number
	Outside this Area Code	Area Code + Number
Directory Assistance Calls	Local	411
	Within this Area Code	800-1212
	Outside this Area Code	Area Code + 800-1212

For Inquiries or Service Visit, SAM - 3PM East  
The number to call is 1-800-543-7344

Elcotel Series 5 is a "LINE POWERED" coin operated "SMART" Pay Telephone. This allows you, the payphone owner to install your Elcotel Series 5 virtually anywhere a telephone line can be installed. There is no hassle or expense of running electrical lines.

Elcotel Series 5 is specifically designed for Quadrum®/GTE® or Western® Electric style housings. So private payphone owners can secure premiere locations and have a payphone that looks and sounds like any other payphone.

### STANDARD FEATURES

- "Line Powered" SMART Coin-operated Payphone
- Quadrum®/GTE® or Western® Electric style housing
- Digitized human voice prompts (not mechanical)
- Superior Answer Detection
- Individual call control "Call Types"
- Pre-defined or custom dialing control "Macros"
- Selectable "Anti-fraud" protection
- Detailed call audit trail "SMDR"
- Cash box full, handset, etc. "Alarms"
- "Service Desk" eliminates refund checks
- Remote Communications - Payphone Network Manager (PNM)

### Payphone Automated Operator Function (PAOF)

- Store-and-Forward Capabilities
- Converts 0+ and collect to 1+
- Validates calls
- Improves revenues

### OPTIONS

- Card Reader
- Volume Control
- Electronic Coin Mechanism
- Panel Phone Enclosure
- Vault Alarm
- Screw down terminal block for TELCO interface

### SPECIFICATIONS

Power: 48V DC Line Voltage  
(On-hook)  
23ma Loop Current  
(Off-hook)  
Note: If the phone line has less than 23 ma current, a DC transformer can be added.  
Line Interface: Standard B-1 or COCOT (RJ11 Terminated)  
Phone Dimensions: 21" x 7 5/8" x 6"  
Weight: 48 lbs.  
Handset: Hearing Aid Compatible  
Ringer Equivalency: 0.7B  
FCC Registration Number: E2DUSA-61027-CX-E

## TELECOMMUNICATIONS SYSTEMS



THE HIGH TECHNOLOGY STORE, INC.  
P.O. Box 11011, Washington, DC 20036  
1-800-764-4507  
(202) 757-4507